

MyCableMart.com

Your Home Theatre Connectivity Experts
6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

CAT6A SHIELDED ETHERNET RJ45 PATCH CABLE,STRANDED,SNAGLESS BOOTED,GRAY



Lengths Available:	6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 7ft, 10ft, 14ft, 20ft, 25ft, 30ft, 35ft, 40ft, 50ft, 60ft, 75ft, 100ft, 150ft, 200ft,		
Colors Available:	Black, Black, Gray,		
Part Numbers this model:	HA-C6A-06IN-GRY, HA-C6A-01-GRY, HA-C6A-02-GRY, BE-100853GY , BE-100854GY, HA-C6A-05-GRY, BE-100856GY, HA-C6A-07-GRY, HA-C6A-10-GRY, HA-C6A-14-GRY, HA-C6A-20-GRY, FE-C6A-25-GRY, FE-C6A-30-GRY, BE-100862GY, FE-C6A-40-GRY, FE-C6A-50-GRY, FE-C6A-60-GRY, HA-C6A-75-GRY, HA-C6A-100-GRY, FE-C6A-150-GRY, HA-C6A-200-GRY,		
Sales Category:	CAT 6 Networking Cables	Wire Gauge (AWG):	26 AWG
Connector A:	RJ45 Ethernet Male	Specification:	
Connector B:	RJ45 Ethernet Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:	Molded Plugs	Images Length/Size Shown:	3 FT
# Positions:	8p8c (RJ45, Ethernet)	Shielding:	Unshielded
Convert From/To:		Type:	Plug to Plug

The latest standard from the TIA for enhanced performance standards for twisted pair cable systems was defined in February 2008 in ANSI/TIA/EIA-568-B.2-10. Category 6a (or Augmented Category 6) is defined at frequencies up to 500 MHz $\frac{1}{2}$ "twice that of Cat. 6.

Category 6a performs at improved specifications, in particular in the area of alien crosstalk as compared to Cat 6 UTP (unshielded twisted pair), which exhibited high alien noise in high frequencies.

Connects any CAT6A (or CAT5E, CAT6) application such as computer to hub, patch panel or wall jack. This 500MHz CAT6A PVC stranded patch cord meets TIA/EIA-568-B-2-10 class EA ISO/IEC 11801, CENELEC EN 50173 and IEEE802.3an specifications, and support all CAT6A and other high speed applications. It has stranded wires for added cable flexibility. Cable is FOIL SHIELDED with drain wire.

Technical Specifications:

- Performance conforms to proposed Cat.6A channel requirement of TIA/EIA-568-B-2-10 class EA ISO/IEC 11801, CENELEC EN 50173 and IEEE802.3an
- 26AWG stranded copper wire
- UL listed
- RoHS compliant
- Double shielded: Each pair foil shielded / 4 pair braid shielded
- 50 micron gold plated RJ45 shielded plug
- Molded snagless boot