

MyCableMart.com

Your Home Theatre Connectivity Experts

6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

50FT XLR 3P MALE TO 1/4" TRS (BALANCED) MALE MICROPHONE CABLE



Lengths Available:	3ft, 3ft, 6ft, 6ft, 10ft, 10ft, 15ft, 15ft, 25ft, 25ft, 50ft, 50ft, 100ft,	
Colors Available:		
Part Numbers this model:	FE-ECXLR14-03MM, FE-XLR14MM-03, FE-ECXLR14-06MM, FE-XLR14MM-06, FE-XLR14MM-10, FE-ECXLR14-10MM, FE-XLR14MM-15, FE-ECXLR14-15MM, FE-ECXLR14-25MM, FE-XLR14MM-25, FE-XLR14MM-50 , FE-ECXLR14-50MM, BE-203226,	
Sales Category:	XLR / TRS Cables	Wire Gauge (AWG): Not Specific / Not Applicable

Connector A:	XLR (3-Pin) Male	Specification:	
Connector B:	1/4 in (6.35mm) TRS Stereo Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	50 FT
# Positions:		Shielding:	Shielded
Convert From/To:		Type:	

The XLR connector is a style of electrical connector, primarily found on professional audio, video, and stage lighting equipment. The connectors are circular in design and have between 3 and 7 pins. They are most commonly associated with balanced audio interconnection, including AES3 digital audio, but are also used for lighting control, low-voltage power supplies, and other applications. XLR connectors are available from a number of manufacturers and are covered by an international standard for dimensions, IEC 61076-2-103.[1] They are superficially similar to the older and smaller DIN connector range, but are not physically compatible with them.

XLR Male to 1/4" Stereo Male balanced cable for microphone

- XLR 3P Male to 1/4" TRS Stereo plug
- Wire gauge: 28 AWG
- OD 6mm
- Nickel Plated Connectors