

USB 2.0 TYPE A MALE TO A FEMALE PANEL MOUNT CABLE



Lengths Available:	6in, 6in, 6in, 12in, 18in, 36in, 5ft, ea, ea, ea, each, each,		
Colors Available:			
Part Numbers this model:	FE-USB-PM-6IN, FE-USBB-PM-6IN, FE-USB3-PM-6IN, FE-USBB-PM-12IN, FE-USBB-PM-18IN, FE-USBB-PM-36IN, FE-USB-PM-05 , FE-USB-FCAP, FE-USB3C-FCAP, --FE-USBB-PM, --FE-USB2CC-PM, --FE-USAC-PM,		
Sales Category:	USB Cables	Wire Gauge (AWG):	24 AWG, 28 AWG
Connector A:	USB Standard Type A Male	Specification:	USB 2.0
Connector B:	USB Standard Type A Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	480Mbps
Feature / Style:	2 Screw Locks (2), Data Transfer and Charge, Panel	Images Length/Size Shown:	5 FT
# Positions:		Shielding:	Shielded
Convert From/To:		Type:	

This is a PANEL MOUNT product. Supports USB speed up to 480Mbps.

Technical Specifications:

- USB v2.0 compliant
- Supports Hi-Speed, 480 Mbps
- Connector A: USB 2.0 Male
- Connector B: USB 2.0 Female Panel Mount
- Panel Connector Dimension: 11.8mm Width, 38.0mm Height
- Panel Connector between bolt hole measurement: 29.0mm
- Shielded (Foil), 100% Copper (CU)
- 28AWG(7/0.12BC)*1P + 24AWG(7/0.2BC)*2C+AL+D
- Nickel plated conductors
- 2 Mounting bolts included
- Cable Outer Diameter: 4.5mm
- Color: Black
- RoHS-2 Compliant