

PREMIUM SHIELDED 3.5MM MINI-STEREO TRS MALE TO FEMALE EXTENSION CABLE



Lengths Available:	6in, 10in, 1.5ft, 2ft, 3ft, 6ft, 10ft, 12ft, 15ft, 20ft, 25ft, 35ft, 50ft, 75ft, 100ft,		
Colors Available:			
Part Numbers this model:	FE-PX3MM-MF-6IN, FE-PX3MM-MF-10IN , FE-PX3MM-MF-01, FE-PX3MM-MF-02, FE-PX3MM-MF-03, FE-PX3MM-MF-06, FE-PX3MM-MF-10, FE-PX3MM-MF-12, FE-PX3MM-MF-15, FE-PX3MM-MF-20, FE-PX3MM-MF-25, FE-PX3MM-MF-35, FE-PX3MM-MF-50, FE-PX3MM-MF-75, FE-PX3MM-MF-100,		
Sales Category:	3.5MM & 2.5MM Cables and Adapters	Wire Gauge (AWG):	24 AWG
Connector A:	3.5mm TRS Stereo Male	Specification:	
Connector B:	3.5mm TRS Stereo Female	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:	Stereo (3 Conductor, TRS)	Images Length/Size Shown:	10 IN
# Positions:		Shielding:	-
Convert From/To:		Type:	

Connects any stereo audio devices. Specifically design for computer audio applications, it works with any PC sound card, speaker, headset, portable CD players, and microphone with a **3 conductor (2 black ring) 3.5mm connector**. This PREMIUM SHIELDED cable to protect against electron-magnetic outside interference, has gold plated end connectors, shielded copper (CU) stranded 24AWG cabling, and metal shell connectors designed to deliver PREMIUM AUDIO. This cable type is typically used to EXTEND the length of an existing 3.5mm cable.

Specifications:

- Connectors: 3.5mm (1/8") Male to FEMALE Stereo TRS
- Outer Diameter of Cable: 4.00mm
- Outer Diameter of Metal Shell: 8.4mm
- 3 Conductor, 24AWG Copper (CU)
- Gold Plated Connectors
- End to End shielding (Braided/Foil)
- Insulation Type: PVC 1.00mm
- Cable Spec: 24AWG 7/0.2BC*2C+AL+32/0.1BC OD:3.5MM
- RoHS-3 Compliant