

MyCableMart.com

Your Home Theatre Connectivity Experts

6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

1 WIRE RCA PREMIUM DIGITAL AUDIO SUBWOOFER/VIDEO CABLE IN WALL



Lengths Available:	6in, 12in, 1.5ft, 3ft, 6ft, 10ft, 15ft, 20ft, 25ft, 35ft, 50ft, 75ft, 100ft,		
Colors Available:			
Part Numbers this model:	FE-RCA-1V-6IN, FE-RCA-1V-12IN , FE-RCA-1V-01, FE-RCA-1V-03, FE-RCA-1V-06, FE-RCA-1V-10, FE-RCA-1V-15, FE-RCA-1V-20, FE-RCA-1V-25, FE-RCA-1V-35, FE-RCA-1V-50, FE-RCA-1V-75, FE-RCA-1V-100,		
Sales Category:	Sub-Woofer Cables	Wire Gauge (AWG):	18 AWG
Connector A:	RCA/Phono Male	Specification:	
Connector B:	RCA/Phono Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	
Feature / Style:	Mono	Images Length/Size Shown:	12 IN
# Positions:		Shielding:	Shielded
Convert From/To:		Type:	

This single wire PREMIUM Gold Plated RCA cable is suitable for S/PDIF Audio Connections (Typically an Orange Connector), Legacy Composite Video Connection (normally with a yellow connector), and Sub-Woofer Connectors. This premium cable has braid shielding to prevent electrical interference and shielded 75ohm coax conductors to maximum audio performance. This cable can be bundled together for component audio and video application and also works for sub-woofer applications. It also has molded and Yellow color-coded with gold-plated connectors. It is RoHS-2 compliant

Specifications:

- Connectors: single RCA Plug (male) to single RCA Plug (male)
- 24k Gold Plated 8-cut connectors ensure long-lasting, corrosion-free connections
- Cable Outer Diameter: 7.0mm
- Fully molded connectors provide excellent strain relief
- High-quality coax wire with copper braid shield reduces unwanted noise and distortion
- Gold-plated, RCA connectors give you solid, corrosion-free contact
- Easy installation with non slip rubber grip
- Improves digital signal delivery as compared to standard RCA type audio cables
- True digital signal maintained by high materials and connectors
- 99.999% Pure Copper Non-OFC conductor
- THICK 18AWG 75 Ohm RG6/u Coax Copper Wire
- Conduction Impedance: 3 Ohms
- Pure Copper 99.99%, #144 Braid
- PVC Jacket Outer Diameter: 7.0mm
- High-density double shielding for max rejection of EMI and RFI

What is SPDIF? - S/PDIF (Sony/Philips Digital Interface) is a standard audio transfer file format. It is usually found on digital audio equipment such as a DAT (Digital Audio Tape) machine or audio processing device. It allows the transfer of audio from one file to another without the conversion to and from an analog format, which could degrade the signal quality.