

Your Home Theatre Connectivity Experts

6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

SPEAKER WIRE, 14AWG COPPER ENHANCED LOUD OXYGEN FREE



Lengths Available:	50ft, 100ft, 250ft, 500ft, 500ft,		
Colors Available:			
Part Numbers this model:	FE-SPK-14-50, FE-SPK-14-100 , FE-SPK-14-250, FE-SPK-14-500, WN-AC1402OSPBK1-500,		
Sales Category:	Speaker Wire	Wire Gauge (AWG):	14 AWG
Connector A:	Blunt Cut	Specification:	
Connector B:	Blunt Cut	Number Ports:	N/A
Export Tariff Code (HST):	8544492000	Transfer Rate:	
Feature / Style:		Images Length/Size Shown:	100 FT
# Positions:	2 (1 Pair)	Shielding:	
Convert From/To:		Type:	

Specially designed, high purity, oxygen free copper for wide frequency range, low signal loss and enhanced emphasis on the low end for loud, clear and bold audio reproduction. Our speaker cables bring you the high quality, great performance and excellent value you've come to expect from us.

Specifications:

- Cable Type: Loudspeaker cable
- High Quality Oxygen-free Copper/CCA
- Gauge: 14AWG
- Strand count: 41 wires
- Total OD (Approx): 3.5 x 7.0mm
- Twist type: Multi-twist, rope lay
- Resistance per Meter: 0.0072 ohm
- PVC color: Clear
- Polarity markers: Yes, blue
- Packaging: Rolled on Spool w/ PE wrap.

NOTICE: ***Opened Speaker Wire CANNOT Be Returned or Exchanged. Actual product may differ from photo***

Use the following chart as a guideline when selecting cable gauge (AWG):

Distance in Feet	Receiver & Speaker Impedance								
	4 Ohm			8 Ohm			16 Ohm		
	50-100W	100-250W	250-600W	50-100W	100-250W	250-600W	50-100W	100-250W	250-600W
20	14 AWG	12 AWG	10 AWG	16 AWG	14 AWG	12 AWG	18 AWG	16 AWG	14 AWG
30	12 AWG	12 AWG	10 AWG	16 AWG	14 AWG	10 AWG	18 AWG	16 AWG	12 AWG
50	12 AWG	10 AWG	10 AWG	16 AWG	14 AWG	10 AWG	16 AWG	16 AWG	12 AWG
100	10 AWG	10 AWG	10 AWG	14 AWG	12 AWG	10 AWG	16 AWG	14 AWG	12 AWG

* Substitute 2 runs of 14AWG to equal performance of 10AWG