MyCableMart com

Your Home Theatre Connectivity Experts

6224 Bury Dr, Eden Prairie MN 55346 P. 952-486-8736

ELITE TOSLINK DIGITAL OPTICAL AUDIO CABLE (SPDI/F METAL CONNECTORS





Lengths Available:	1.5ft, 3ft, 6ft, 8ft, 12ft, 15ft, 20ft, 25ft, 30ft, 35ft, 40ft, 50ft, 75ft,			
Colors Available:				
Part Numbers this model:	FE-TOS-01, FE-TOS-03, FE-TOS-06, HA-TOS-08, HA-TOS-12, HA-TOS-15, HA-TOS-20, HA-TOS-25, FE-TOS-30, HA-TOS-35, FE-TOS-40, FE-TOS-50, FE-TOS-75,			
Sales Category:	Optical Cables	Wire Gauge (AWG):	Not Specific / Not Applicable	
Connector A:	Toslink Optical Audio Male	Specification:		
Connector B:	Toslink Optical Audio Male	Number Ports:	N/A	
Export Tariff Code (HST):	8544422000	Transfer Rate:		
Feature / Style:		Images Length/Size Shown:	3 FT	
# Positions:		Shielding:		
Convert From/To:		Туре:		

Connects any sound bar or home theater system with Toslink digital audio port. Works with digital receivers, CD/DVD players, or any other digital audio device with optical connectors.

Toslink is a connector format for fiber optic digital audio cables. A fiber optic digital audio cable carries audio data in the form of light impulses instead of electrical signals. The Toslink connector is a square plug and is used with newer Dolby Digital surround sound receivers, digital versatile discs (DVDs), and compact disk (CD) players, satellite dish receivers, and other devices. Miniplug is another fiber optic digital audio format, similar to Toslink, used for minidisk players and other smaller digital audio devices. Mini-plug adapter **IS NOT** included for this particular length.

Toslink optical cables are the standard for most stereos, home-theatres, sound bars, TVs, DVD/CD players, digital receivers, and satelite receivers.

Product Features

- HEAVY 6.0mm JACKET Helps Prevent Cable Damage and Provides Additional Strain Relief
- Outer Cable Diameter: 6.0mm
- NYLON Braided Sleeve Jacket
- Suitable for in-wall installation
- TL1-5 Toslink Standard End Connectors
- RoHS Compliant (Lead Free)
- GOLD-PLATED FERRULE Prevents Corrosion and Provides for Maximum Protection of the Fiber Tip
- PRECISION POLISHED FIBER TIPS for Maximum Signal Transfer (includes tip protectors)

IMPORTANT PACKAGING NOTE: All our Toslink optical cables are packaged and shipped with clear tip protectors to ensure that no dust or other foreign material gets trapped inside the toslink end connection. Before attempting to connect this cable to your equipment, be sure to REMOVE these protective tips.

NOTE: For most audio systems, you should not hear any diff and transmitting at extreme bandwidth levels. In fact, the pedesigned to interface with POF fibers.	erence between a plastic optical cable a erformance with plastic has been improv	nd a glass quartz optical cable unless ing because the Opto-electrical Compo	your are at lengths exceeding 100 feet onents (used in Audio Equipment) are
designed to interface with POF fibers.			