

USB TYPE-C 90 DEGREE METALLIC BLUE MALE TO TYPE-A MALE CABLES



Lengths Available:	6in, 1.5ft, 3ft, 6ft, 10ft,		
Colors Available:			
Part Numbers this model:	FE-USBM-C27A-6IN, FE-USBM-C27A-01, FE-USBM-C27A-03 , FE-USBM-C27A-06, FE-USBM-C27A-10,		
Sales Category:	USB Cables	Wire Gauge (AWG):	24 AWG, 28 AWG
Connector A:	USB Standard Type A Male	Specification:	USB 2.0
Connector B:	USB Standard Type A Male	Number Ports:	N/A
Export Tariff Code (HST):	8544422000	Transfer Rate:	480Mbps
Feature / Style:	Data Transfer and Charge	Images Length/Size Shown:	3 FT
# Positions:		Shielding:	Shielded
Convert From/To:		Type:	

The USB 3.1 standard introduces the new symmetrical/reversible Type C connector. The new connector is only slightly larger than the older mini and micro Type B connectors, which means that it can be used on mobile devices, replacing the existing use of mini or micro connectors. The USB type-C connector is symmetrical, which means no more fumbling around to figure out which side is supposed to be on top. Just grab either end and plug it in! The ANGLE feature is great when plugging in smart-phones at the bottom and having them rest in cars as the leveled edge of the angled C connector will keep the phone level. Extended Type-C connector allows use of this cable with most phone cases

When comparing our cables to our competitors, please note the WIRE THICKNESS of 28AWG (1P) + 24AWG*2C. Most of our competitors use 28/28AWG cables resulting in signal loss, slower charging times, and overall amperage loss.

This USB 2.0 cable features a male 90 degree angled USB Type C connector on one end, and a USB 2.0 (480Mbps) Type A Male Angled connector at the other end.

- Use a single cable for power, video, networking, and data
- Angled End Dimension: 18.3mm x 19mm (see tech drawing for complete specs)
- Extended Type-C connector allowing for use with case
- Polished aluminum metallic blue angled connectors
- Protective nylon cable net jacket
- USB 2.0 supports up to 480Mbps data rate
- Supports Super Fast Charging and Syncing
- 28AWG (7/0.12mm Bare Copper) * 1 Pair (for Data), 24AWG (7/0.2mm Bare Copper) * 1C (for power), Drain Wire (7/0.2mm Bare Copper)
- USB Standard: 2.0
- RoHS 2.0 Compliant
- Type: USB Type C male 90 degree angled to USB 2.0 Type A male angled
- Power Rating: Up to 5V, 2A