

Product Specification

Item no	215010	Description:	6 Outlet Power Strip with Surge		
Photo(s)		Color	Grey	Indent Marking based on cULus or equivalent standard	
		Raw Material	(ETL)us ETL# SJT 3X14AWG 60°C 300V VW-1 c(ETL) SJT 3X2.08mm ² (14AWG) FT2		
		Plastic: ABS 110g			
		Copper Strip: 11g			
Key Features & Specs		ON/OFF Switch: with Light	Compound Requirement		
Male Blades:UL CUL Recognized Components(NEMA-5-15P)		Cabel: 3C SJT 14AWG 2.5FT	PVC 60°C Insulation Compound		
Female Contacts:UL CUL Recognized Components(NEMA-5-15P)			Approved for SJT Cable		
Female Ground:UL CUL Recognized Components(NEMA-5-15P)		Jacket Construction	Cold Bend Test Requirement		
Label:UL CUL required		100% Fully Pressure Extruded Jacket	Must pass cold bend test at -20°C		
Agency Approvals:ETL Listing					
Rate: AC 15A 125V 60Hz 1875W					
Maximum Surge: 7000Amp 6000V,90J					
	Test	Hipot test @1.5KV			
		Power test @ with light can light			
		Drop test @70cm			
		Grounded test@ with ground requirement			
ETL file #	UL file #	CSA/UL file #		Date:	2011.11.15
	E308551				