



- NOTES:
- 100% OPEN & SHORT TESTING
  - VOLTAGE: 300V DC
  - INSULATION RESISTANCE: 20M ohm
  - CONTACT RESISTANCE: 5 ohm

CUSTOMER P/N	length
FE-C690-01-BLK	1FT(305MM±30MM)
FE-C690-02-BLK	2FT(610MM±30MM)
FE-C690-03-BLK	3FT(915MM±30MM)
FE-C690-05-BLK	5FT(1520MM±30MM)
FE-C690-07-BLK	7FT(2130MM±50MM)
FE-C690-10-BLK	10FT(3050MM±50MM)
FE-C690-14-BLK	14FT(4270MM±80MM)
FE-C690-20-BLK	20FT(6150MM±100MM)
FE-C690-25-BLK	25FT(7620MM±100MM)

## MY CABLE MART LLC

8		
7		
6		
5		
4		PE BAG+LABEL
3		PCV45Pa BLACK
2		CAT6 RJ45 MALE
1		CAT.6 UTP CABLE 24AWG(7/0.18BC)*4P+CROSS.+. . OD: 6.0MM BLACK
NO.	Material	Description

Title: CAT6 ANGLED-UP NETWORK PATCH CORD			
Customer: MY CABLE MART LLC		Page: 1/1	Drawn BY: CLR
Customer P/N:		REV: A1	Check BY: DYH
Date: 2016.08.15	Drawing NO: FLFU90	Unit: mm	Appd BY: