



- AL+MY:5\*(8+1)al/my/my
- insulation:5pairs,FPE,OD:Ø0.75±0.02
- conductor:5Cx[30AWG(1/0.254CUx1pair)]
- conductor:5Cx[30AWG(1/0.254CUx1pair)]
- conductor:4Cx30AWG(0.254CU)
- insulation:7 core, OD:Ø0.6±0.03, HDPE(1 twisted)
- AL/MY:AL/MY, 0.025\*30mm
- DRAIN:0.254Cu**
- DRAIN:16/8/0.12AL**
- jacket:Ø5.5±0.15mm
- UL PVC,75P, black

- FE-DVI-HM-01 450(1.5FT)+/-20MM
- FE-DVI-HM-03 905(3FT)+/-30MM
- FE-DVI-HM-06 1830(6FT)+/-50MM
- FE-DVI-HM-10 3050(10FT)+/-80MM
- FE-DVI-HM-15 4570(15FT)+/-100MM

DVI	Signal Assignment	HDMI c V1.4
2 Red	—	Red 2
3 Earth	—	Earth 1
1 White	—	White 3
10 Blue	—	Blue 5
11 Earth	—	Earth 4
9 White	—	White 6
18 Green	—	Green 8
19 Earth	—	Earth 7
1 White	—	White 9
23 Brown	—	Brown 11
22 Earth	—	Earth 10
24 White	—	White 12
6 Black	SCL	Black 15
7 Yellow	SDA	SDA Yellow 16
15	Orange	Orange 17
16	Purple	Purple 19
14	Red	+5 Volts Power Red 18
20		20

NO.	DRAW	SPEC	QTY
5		DVI PLUG	1PCS
4		HDMI Cable 30AWG	1PCS
3		TYPE g(P) OUTER MOLD	1SET
2		TYPE c(P) INNER MOLD	1PCS
1		HDMI TYPE c PLUG	1SET

DES.	MTL.	MDL
CHK	TRL.	PDT
APPR.	VER	.TIT
<b>MY CABLE MART LLC</b>		
Unit: MM	Page 1	Pages 3
	A-1	SCL
		SPEC
		DVI to mini hdmi C